

NÖ. NEXT ASSY USED ON LTR DESCRIPTION DATE APPROVED C INCORPORATED ECN 24229 1.52 [38.55] .40 [10.16] .759 [19.28] .20 [5.08] RPD-9-S SN: XXXXXXX Ø.093 [Ø2.36] THRU			₩		
C INCORPORATED ECN 24229 1.52 [38.55] .40 [10.16] .759 [19.28] .20 [5.08] RPD-9-S SN: XXXXXXX Ø.093 [Ø2.36] THRU	חרטוו — — — — — — — — — — — — — — — — — —				
1.52 [38.55] .40 [10.16] .759 [19.28] .20 [5.08] RPD-9-S SN: XXXXXXX Ø.093 [Ø2.36] THRU	NO. NEXT ASSY USED ON	 	DESCRIPTION		
1.45 [36.78] 1.45 [36.78] 0.093 [\$\pi 2.36] THRU	1 1	C INCORF	PORATED ECN 24229	06/25/12	J. Campisi
CONNECTORS ON 1.448 DIA. B.C.	SMA FEMALE	— 1.52 [38.55 33 √4	7.759 [19.28] 36° TYP Ø.093 [Ø2.36] THRU MOUNTING HOLES	.40 [10.16]-	

SIZE

Α

SCALE

1

APPROVAL (PROJ)

APPROVAL (GOVT)

CODE IDENT. NO.

REV.

33592

SHEET 1 OF